



## 400A, 11KV, POLYMERIC G.O. AIRBREAK SWITCH

1	MOVING MALE CONTACTS 35 mm x 6 mm	: COPPER SILVER PLATING
2	FIX FEMALE CONTACTS 38 mm x 3 mm	: COPPER SILVER PLATING
3	POAT INSULATOR CRIPAGE DISTANCE 320 mm	: POLYMERIC 2 NOS.
4	ALL M.S.PART	: HOT DIP (G.I.)
5	BASE CHANEL - 75 mm x 40 mm x 410 mm - (M. S.)	: HOT DIP (G.I.) 865 mm
6	BASE FOR MALE CONTACT - 33 mm x 9 mm x 153 mm	: GUN METAL TIN PLATING
7	BASE FOR FEMALE CONTACT - 33 mm x 9 mm x 133 mm	: GUN METAL TIN PLATING
8	TERMINAL CONNECTOR FOR CONDUCTOR	: PALM TYPE CONNECTOR
9	AMPERE CAPACITY	: 400 AMP
10	BASE FOR MOVING INSULATOR	: M.S.G.I.
11	ARCING HORN	: M.S. HOT DIP
12	DISTANCE BETWEEN TWO PHASES	: 550 mm
13	ISOLATING DISTANCE BETWEEN MOVING & FIX CONTACTS	: 350 mm

**UGVCL**  
Uttar Gujarat Vij Company Ltd.