



REGISTERED & CORPORATE OFFICE MEHSANA -384001

PHONE : 02762-222080/81/97 FAX :223574

SCHEDULE B

NAME OF WORK : CONSTRUCTION OF TYPE - 3 QUARTERS AT PALANPUR.

SR. NO.	DESCRIPTION	QTY.	UNIT	RATE	AMOUNT
SH : I EARTH WORK :					
1.01	Excavation for foundation upto 1.5 M. depth incl. sorting out and stacking of useful materials and disposing of excavated stud up to 50M. lead. Dense or hard soil.	250.00	Cum.	59.50	14875.00
1.02	Excavation for foundation for depth from 1.5 Mt to 3 Mt. depth incl. sorting out and stacking of useful materials and disposing of the excavated stuff upto 50Mt. lead. Hard murrum	110.00	Cum.	109.00	11990.00
1.03	Filling available excavated earth (excl. rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20 cm. In depth consolidating EA deposited layer by ramming and watering.	360.00	Cum.	29.90	10764.00
1.04	Filling in foundation and plinth with murrum or selected soil in layers of 10 cm. Thickness incl. watering ramming and consolidating etc. comp.	75.00	Cum.	230.00	17250.00
1.05	Filling in plinth with sand under floors including watering, ramming, consolidating and dressing etc. complete.	55.00	Cum.	421.00	23155.00
SH : II CEMENT CONCRETE :					
2.01	Providing and laying cement concrete 1:4:8 (1cement : 4coarse sand : 8 hand broken stone aggregates 40 mm. nominal size) and curing complete including cost of from work in foundation & plinth.	75.00	Cum.	1759.00	131925.00
2.02	Providing and laying cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm. Nominal size) laid in one layer finished with a floating coat of neat cement--50mm. .	80.00	Sqm.	177.00	14160.00
SH : III REINFORCED CEMENT CONCRETE :					
3.01	Providing and laying C.C. M-200 and curing complete incld. the cost of form work and reinforcement for RC work in : Foundations, footings Bases of columns and the like and Mass concrete.	40.00	Cum.	3060.00	122400.00
3.02-A	Providing and laying cement concrete M-200 and finishing smooth with curing etc. complete including the cost from work but excluding the cost of reinforcement for R.C.C. work in Slabs having more than 10 cm. And up to 13 cm. Thicknes up to floor two level.	35.00	Cum.	4123.00	144305.00

3.02-B	Providing and laying cement concrete M-200 and finishing smooth with curing etc. complete including the cost from work but excluding the cost of reinforcement for R.C.C. work in Slabs having more than 10 cm. And up to 13 cm. Thickness for floor two to three level.	35.00	Cum.	4150.30	145260.50
3.02C	Providing and laying cement concrete M-200 and finishing smooth with curing etc. complete including the cost from work but excluding the cost of reinforcement for R.C.C. work in Slabs having more than 10 cm. And up to 13 cm. Thickness for floor three to four level.	3.00	Cum.	4177.60	12532.80
3.03A1	Providing and laying cement concrete M-200 and finishing smooth with during etc. complete including the cost of work but excluding the cost of reinforcement for R.C.C. work in Beams having cross sectional area more than 0.12 sq.M. & up to 0.18 Sq.M. up to floor two level	50.00	Cum.	4595.00	229750.00
3.03A2	Providing and laying cement concrete M-200 and finishing smooth with during etc. complete including the cost of work but excluding the cost of reinforcement for R.C.C. work in Beams having cross sectional area more than 0.12 sq.M. & up to 0.18 Sq.M. up to floor two to three level.	25.00	Cum.	4622.30	115557.50
3.03B1	Providing and laying cement concrete M-200 and finishing smooth with during etc. complete including the cost of work but excluding the cost of reinforcement for R.C.C. work in Beams having cross sectional area more than 0.08 sq.M. & up to 0.12 Sq.M. up to three to four level	2.00	Cum.	5278.60	10557.20
3.04A	Providing and laying cement concrete M-200 and finishing smooth with curing etc.. Complete including the cost of form work but excluding the cost of reinforcement for R.C.C. LINTEL /coping / stair case up to floor two level.	15.00	Cum.	5083.00	76245.00
3.04B	Providing and laying cement concrete M-200 and finishing smooth with curing etc.. Complete including the cost of form work but excluding the cost of reinforcement for R.C.C. LINTEL /coping / stair case for floor two to three level.	15.00	Cum.	5110.30	76654.50
3.05A	Providing and laying cement concrete M-200 for reinforces concrete chajjas not exceeding 10 cm. Thickness up to floor two level including finishing the exposed surfaces with cement mortar 1:3 (1cement :3 fine sand) to give a smooth surface centering and form work and curing complete excluding cost of reinforcement. up to floor two level.	2.00	Cum.	4532.00	9064.00
3.05B	Providing and laying cement concrete M-200 for reinforces concrete chajjas not exceeding 10 cm. Thickness up to floor two level including finishing the exposed surfaces with cement mortar 1:3 (1cement :3 fine sand) to give a smooth surface centering and form work and curing complete excluding cost of reinforcement. floor two to three level.	2.00	Cum.	4559.30	9118.60

3.06A	Providing and laying cement concrete M-200 and finishing smooth with during etc. complete including the cost of work but excluding the cost of reinforcement for R.C.C. work in columns having cross sectional area more than 0.12 sq.m. up to floor two level.	25.00	Cum.	4113.00	102825.00
3.06B	Providing and laying cement concrete M-200 and finishing smooth with during etc. complete including the cost of work but excluding the cost of reinforcement for R.C.C. work in columns having cross sectional area more than 0.12 sq.m.floor two to three level.	15.00	Cum.	4140.30	62104.50
3.06C	Providing and laying cement concrete M-200 and finishing smooth with during etc. complete including the cost of work but excluding the cost of reinforcement for R.C.C. work in columns having cross sectional area more than 0.12 sq.m. floor three to four level.	2.00	Cum.	4167.60	8335.20
3.08	Providing T M T. bar reinforcement for R.C.C. work including vending binding and placing in position complete up to floor two level.	30000.00	Kgs.	50.60	1518000.00
SH : IV BRICK WORK :					
4.01	Brick work using common Brunt clay building bricks having crushing strength not less than 35 Kg./Sqcm. In foundation and plinth in cement mortar 1:6 (1cement : 6 fine sand)	35.00	Cum.	2013.00	70455.00
4.02A	Brick work using common Brunt clay building bricks having crushing strength not less than 35 Kg./Sqcm. In super structure above plinth level in cement mortar 1:6 (1cement : 6 fine sand) up to floor two level.	65.00	Cum.	2077.60	135044.00
4.02B	Brick work using common Brunt clay building bricks having crushing strength not less than 35 Kg./Sqcm. In super structure above plinth level in cement mortar 1:6 (1cement : 6 fine sand) for floor two to floor three level.	65.00	Cum.	2097.60	136344.00
4.02C	Brick work using common Brunt clay building bricks having crushing strength not less than 35 Kg./Sqcm. In super structure above plinth level in cement mortar 1:6 (1cement : 6 fine sand) for floor three to floor four level.	35.00	Cum.	2117.60	74116.00
4.03A	Half brick masonry in common brunt clay building bricks having crushing strength not less than 35 Kg./Sqcm. In cement mortar 1:4 (1cement : 4 coarse sand) in super structure up to floor two level.	125.00	Sqm	290.40	36300.00
4.03B	Half brick masonry in common brunt clay building bricks having crushing strength not less than 35 Kg./Sqcm. In cement mortar 1:4 (1cement : 4 coarse sand) in super structure for floor two to three level.	125.00	Sqm	293.20	36650.00
SH : V WOOD WORK : DOORS / WINDOWS					
5.01	Providing and fixing built in wall teak wood cupboard shutters having 75x50 mm teak wood frame and shutter with 19mm thick block board with 01mm thick laminated sheet on front side and fixing the same by adhesive & necessary hardware incl T.W. beading etc completed.	40.00	Sqm	2500.00	100000.00

5.02	Providing & fixing 35 mm. Thick shutters for doors, windows and clearstory windows including indian teak wood frames 12 cm. X 7 cm. Size including iron Chromium plated fixtures & fastenings including primer coat of approved quality and two coats of oil paint etc. complete fully pannelled door .	40.00	Sqm	4010.00	160400.00
5.03	Providing and fixing PVC door frame of size 48X40X1.80MM thick for PVC door with inserting country wood in hollow part with approved size of corner, necessary hole fast & grouting in wall etc. complete as directed. (Measurement will be paid for width out to out without horns and height from floor top surface to top of frame. Item to be used for W/C and bath only.)	15.00	Sqm	632.50	9487.50
5.04	Providing and fixing PVC door shutter in single or double leaf of 20mm thick with shutter outer frame top bottom and style of size 54 X 24 X 1.80mm thick and locking rail ara of size 100 X 24 X 1.80mm thick panels are made from PVC section 200 X 20 X 1mm thick including fixing & joints with providing 3 Nos. of 100 mm long hinges on each flap of door including fixing with frame. The material is f approved ISI brand colour & tint as per drawing & instruction of E.I.C. (To be used for bath & W/C only. Measurement shall be paid for clear size of shutter only.)	14.00	Sqm	1237.50	17325.00
5.05	Providing & fixing 35 mm. Thick shutters for doors, windows and clearstory windows including indian teak wood frames 10 cm. X 7 cm. Size including iron chromium plated oxidise fixtures & fastenings including primer coat of approved quality and two coats of oil paint etc. complete partly pannelled windows.	55.00	Sqm	3486.00	191730.00
SH : VI STEEL WORK :					
6.01	Providing & fixing M.S. grills of required pattern to wooden frames of windows etc. with M.S. flats at required spacing and frame all-round square or round bars with round headed bolts and nuts or by screws.(a) Plain grill	1400.00	Kg.	64.00	89600.00
SH : VII FLOORING :					
7.01	Providing and laying Kota stone slab flooring over 20 mm. (average thick base of cement mortar 1:6 (1 cement : 6 coarse sand) or L.M. 1:1.5 and laid over and jointed with grey cement slurry including rubbing and polishing complete.(A) 25 mm . Thick	350.00	Sqm.	581.00	203350.00
7.02	Providing and laying Kota stone slab 25 mm. Thick in resiers of steps. Dado and pillars laid on 10 mm. Thick cement mortar 1:3 (1 cement : 3 coarse sand) and jointed with grey cement slurry including rubbing and polising etc. complete.	50.00	Sqm.	650.00	32500.00
7.03	Providing and laying approved colour glazed tiles 6 mm. Thick inflooring treads of steps and landings laid on a Bed of 12 mm. Thick cement mortar 1:3 (1 cement : 3 coarse sand) pointing in white ceand jointed with white cement slurry.	15.00	Sqm.	604.00	9060.00

7.04	Providing and laying approved colour glazed tiles 6 mm. Thick in skirting risers of steps and dado on 10 mm. Thick cement plaster 1:3 (1 cement : 3 coarse sand) pointing in white ceand jointed with white cement slurry.	125.00	Sqm.	617.00	77125.00
SH : VIII ROOFING					
8.01	Providing & fixing china mosaic tiles flooring as water proofing treatment including (a) Applying cement slurry of cement admixed with water proofing compound after cleaning the surface properly. (b) Cracks in slab shall be open in ' V ' groove & all loose materials shall be removed & crack filling shall be done with special & approved type of expanding crack fillet material . (c) Depressions in slab if any be filled up with C.C.(1:2:4) I.P.S.flooring. (d) P / L 20 mm thick plaster layer in C.M. (1:4) with cement admixed with water proofing compound including rounding of junction of walls and slab by making cement vata. (e) Finishing the surface with china mosaic tiles (pieces) flooring incl.fixing the same in cement mortar (1:2) setting with ready made tile adhesive as recommended by manufacturer's including fillings of joints mixed with pigmented white cement slurry of matching shade & finally finishing the surface with trowel with white cement slurry etc., complete (f) After finishing, the whole terrace shall be flooded with water to check the performance of work.	230.00	Sqm.	320.00	73600.00
SH : IX FINISHING :					
9.01A	Providing 15 mm. Thick cement plaster in single coat on fair side Brick/concrete walls for interior plastering upto floor two level and finished even and smooth in :Cement mortar 1:3 up to floor two level.	600.00	Sqm.	100.40	60240.00
9.01B	Providing 15 mm. Thick cement plaster in single coat on fair side Brick/concrete walls for interior plastering upto floor two level and finished even and smooth in :Cement mortar 1:3 floor two to three level.	600.00	Sqm.	106.60	63960.00
9.01C	Providing 15 mm. Thick cement plaster in single coat on fair side Brick/concrete walls for interior plastering upto floor two level and finished even and smooth in :Cement mortar 1:3 floor three to four level.	175.00	Sqm.	112.80	19740.00
9.02A	Providing 15 mm. Thick cement plaster in single coat on celing and soffits of stairs for interior plastering upto floor two level and finished even and smooth in :Cement mortar 1:3 up to floor two level.	200.00	Sqm.	107.00	21400.00
9.02B	Providing 15 mm. Thick cement plaster in single coat on celing and soffits of stairs for interior plastering upto floor two level and finished even and smooth in :Cement mortar 1:3 floor two to three level.	200.00	Sqm.	113.20	22640.00
9.02C	Providing 15 mm. Thick cement plaster in single coat on celing and soffits of stairs for interior plastering upto floor two level and finished even and smooth in :Cement mortar 1:3 floor three to four level.	30.00	Sqm.	119.40	3582.00

9.03	20 mm. Thick sand faced cement plaster on walls upto height 10 meters above ground level consisting of 12 mm. Thick backing coat of c.m. 1:3 (1 cement : 3 sand) and 8 mm. Thick finishing coat of c.m. 1:1 (1 cement : 1 sand) etc. complete.	600.00	Sqm.	141.00	84600.00
9.04	Providing cement vata (10 cm x 10 cm size) quartar round in cement mortar 1:1 incl. neat cement finishing watering etc. complete.	75.00	Rmt.	14.10	1057.50
9.05	Distempering (Three coats) with oil bound distemper of approved brand & manufacture & of required shade on wall surfaces to give an even shade, over & including a priming coats with a distemper primer of approved brand & manufacture after thoroughly brushing the surface free from mortar dropping & other foreign matter & also including preparing surface even & sand papered smooth,incl lappi putty.	1400.00	Sqm.	64.1	89740.00
9.05A	Distempering (Three coats) with oil bound distemper of approved brand & manufacture & of required shade on CELLING surfaces to give an even shade, over & including a priming coats with a distemper primer of approved brand & manufacture after thoroughly brushing the surface free from mortar dropping & other foreign matter & also including preparing surface even & sand papered smooth.	425.00	Sqm.	49.6	21080.00
9.06	Providing & applying 1 coat of approved make of cement primer paint including scaffolding etc., complete as directed by E.I.C.	750.00	Sqm.	13.2	9900.00
9.07	Providing & applying 2 coats of APEX or its equivalent AACRYLIC EXTERIOR paint on exiting plastered surface or approved makes & shade including finishing & thining as per manufacturers instruction. A gap of 6 hrs. should be given between 2 subsequent coats. The work should be carried out strictly as per manufacturers specifications and requirement etc., complete as directed by E.I.C.	750.00	Sqm.	60.50	45375.00
9.08	Painting two coats (including priming coat) on new steel and other metal surfaces with enamel paint, brushing interior to give an even shade including cleaning the surface of all dirt, dust and other foreign matter.	55.00	SMT.	69.4	3817.00
SH : X W/S & SANITATION FIXTURES :					
10.01	Providing and fixing cast iron (spun) Nahni trap of the following nominal diametre of seld cleaning design with C.I.screwed down or highd grating including cost of cutting and making good the walls and floors 100 mm. Inlet and 50 mm. Outlet.	16.00	No.	316.00	5056.00
10.02	Providing and fixing water closet squatting pan (Indian type W.C.pan) size 580 mm. (A) Vitereous china (i) Long pattern in approved colour, with Providing and fixing 100 mm. Size 'P' or 'S' trap for water closet squatting pan & foot rest including jointing the trap with the pan and soil pipe in cement mortar 1:1 (1 cement : 1fine sand) ,	4.00	No.	761.00	3044.00

10.03	Providing and fixing wash basin with single hole for pillar tap with C.I. Or M.S. brackers painted white including cutting holes and making good the same but including fittings like 15mm. C.P. brass pillar tap, stop cock, 32mm brass waste coupline with waste pipe etc.. complete. (A) Vitreous china (ii) Flat back wash basin 500mm x 400mm size IN APPROVED COLOUR.	4.00	No.	895.00	3580.00
10.04	P & F chromium plated bottle trap with necessary coupling of approved quality for wash basin	4.00	No.	351	1404.00
10.05	Providing and fixing 600 mm. X 450 mm. Bevelled edge mirror of superior glass mounted on 6 mm. Thick A.C, sheet or plywood sheet and fixed to wooden plugs with C.P. brass screws and washers	4.00	No.	573.00	2292.00
10.06	Providing and fixing screw down bib taps Brass chromium plated screw down bib tap- 15mm dia	16.00	No.	235.00	3760.00
10.07	Providing and fixing C.P. brass towel rail 600mm x 20 mm complete with C.P. Brass brackets fixed to wooden plugs with C.P. Brass screws,	4.00	No.	454.00	1816.00
10.08	P & F S.W. Gully trap with C.I. Grating brick masonry chamber and water tight C.I. Cover with frame of 300 mm. X 300 size (inside) with standard weight (I) Square mouth trap (A) 150 mm. X 100 mm. Size p -- type	4.00	No.	1050.00	4200.00
10.09	Constructing brick masonry chamber for under ground C.I. Inspection chamber and bends with bricks having crushing strength not less than 35 Kg/cm ² in cm. 1:5 C.I. Cover with frame (light duty) 455 mm. X 610 mm. Internal dimensions, total weight of cover with frame to be not less than 38 Kgs. weight of cover 23 Kg. and wt. of frame 15 Kg) R.C.C. tiop slab with 1:2:4 mix(1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm. size) foundation concrete 1:5:10 inside plaster 15 mm. thick with cement mortar 1:3 finished smooth with a floating coat of neat cement on walls & abed concrete etc. complete. (I) inside dimensions, 455 mm. 610 mm. And 450 mm. Deep for single pipe line	4.00	No.	2141.00	8564.00
10.10	Providing every additional depth of 0.1 mtr Or part thereof beyond 450 mm. Depth for brick masonry chamber.(I) for 445 mm. X 610 mm. Size	20.00	No.	148.00	2960.00
10.11	Providing and fixing to wall, ceiling and floor 6.0 Kg f/cm ² working pressure polythelene pipes of the following outside dia. Low density, complete with special flange compression type fittings wall clamps etc. including making good the wall, ceiling and floor.(A) 110 mm. 10.0 Kg/cm ²	90.00	Rmt.	312.00	28080.00
10.12	Providing and fixing 25mm dia chromium plated brass half turn flush cock of approved quality incl. fixing in pipe line etc. complete.	4.00	Each	374.00	1496.00

10.13A	Providing and laying (Two level or slopes) and jointing with stiff mixture or cement mortar in proportion 1:1, salt glazed stone ware pipes 100 mm dia. nominal intrnal diametre including testing of pipes and joints etc. complete.	20.00	Rmt.	125.00	2500.00
10.13B	Providing and laying (Two level or slopes) and jointing with stiff mixture or cement mortar in proportion 1:1, salt glazed stone ware pipes of 150 mm dia. nominal intrnal diametre including testing of pipes and joints etc. complete.	40.00	Rmt.	179.00	7160.00
10.13C	P & L CC 1:5:10 (1 cement : 5 fine sand : 10 graded stone aggregate 40 mm. Nominal size) bedding for stone- ware pipes of 100 mm dia.(112 mm Average bed thickness)	20.00	Rmt.	75.90	1518.00
10.13D	P & L CC 1:5:10 (1 cement : 5 fine sand : 10 graded stone aggregate 40 mm. Nominal size) bedding for stone- ware pipes of 150 mm dia.(116 mm Average bed thickness)	40.00	Rmt.	128.00	5120.00
10.14	Providing and laying in tenches glavanised mild steel tubes (medium grade) of 15mm dia of the following nominal bore, and tube fittings	50.00	Rmt.	145.00	7250.00
10.15	Providing and laying in tenches glavanised mild steel tubes (medium grade) of 20mm dia of the following nominal bore, and tube fittings	50.00	Rmt.	182.00	9100.00
10.16	Providing and laying in tenches glavanised mild steel tubes (medium grade) of 25mm dia of the following nominal bore, and tube fittings	100.00	Rmt.	255.00	25500.00
10.17	Providing and laying in tenches glavanised mild steel tubes (medium grade) of 40mm dia of the following nominal bore, and tube fittings	5.00	Rmt.	387.00	1935.00
10.18	Providing and laying in tenches glavanised mild steel tubes (medium grade) of 50mm dia of the following nominal bore, and tube fittings	5.00	Rmt.	498.00	2490.00
10.19A	Providing and fixing to wall, ceiling and floor 6.0 Kg f/cm2 working pressure polythelene pipes of 20 mm. 6 Kg/cm2 outside dia. Low density, complete with special flange compression type fittings wall clamps.	10.00	Rmt.	44.00	440.00
10.19B	Providing and fixing to wall, ceiling and floor 6.0 Kg f/cm2 working pressure polythelene pipes of 25 mm. 6 Kg/cm2 outside dia. Low density, complete with special flange compression type fittings wall clamps.	10.00	Rmt.	55.00	550.00
10.19C	Providing and fixing to wall, ceiling and floor 6.0 Kg f/cm2 working pressure polythelene pipes of 50 mm. 6 Kg/cm2 outside dia. Low density, complete with special flange compression type fittings wall clamps.	20.00	Rmt.	110.00	2200.00
10.19D	Providing and fixing to wall, ceiling and floor 6.0 Kg f/cm2 working pressure polythelene pipes of 75 mm. 6 Kg/cm2 outside dia. Low density, complete with special flange compression type fittings wall clamps. For drainage	60.00	Rmt.	171.00	10260.00
10.20A	Providing and fixing in position cowlvent to pipes : 75 mm	4.00	Each	352.00	1408.00
10.20B	Providing and fixing in position cowlvent to pipes : 100 mm	4.00	Each	479.00	1916.00
10.21A	Providing and fixing 15mm dia gun metal check or nonreturn fullway wheel valve	5.00	Each	229.00	1145.00
10.21B	Providing and fixing 20mm dia gun metal check or nonreturn fullway wheel valve	5.00	Each	246.00	1230.00
10.21C	Providing and fixing 25mm dia gun metal check or nonreturn fullway wheel valve	5.00	Each	467.00	2335.00

10.21D	Providing and fixing 40mm dia gun metal check or nonreturn fullway wheel valve	1.00	Each	757.00	757.00
10.22	Providing and fixing ball cock of approved quality as directed- Copper metal 25mm dia	4.00	Each	317.00	1268.00
10.23	Providing & Fixing readymade P.V.C. water tight storage tank made from linear low density polyethylene & low density polyethylene LDPF product confirming to I.S: 10146-1982 with cover including providing & fixing one 20mm.dia. float valve ball-cock ,one 20mm.dia. G.I. Waste pipe with plug one 25mm.dia.G.I.Over flow pipe of length up to 0.30Mt.including making all connection for inlet/outlet supply with necessary fittings for outlet/ inlet etc., complete as directed by E.I.C. 1000 litre capacity.	4.00	No.	4400.00	17600.00
10.24	Providing & fixing 20cm x 15cm x 2.5 thick year plate of marble stone set in CM 1:4 including finishing and engraving letters, etc complete.	1.00	No	176.00	176.00
10.25	Constructing a cooking platforms 60cm width and 70cm height resting on B. B. masonry walls 23cm thick in CM (1:6) with fixing Kadappa stone 30mm thick laid on pre-cast RCC (1:2:4) slab with plastering on exposed faces of wall in CM (1:4), etc complete.	30.00	Rmt	1729.00	51870.00
10.26	Applying general insecticides pest control treatment to floors, cupboards, etc including labour, materials, etc complete.	250.00	Smt	43.60	10900.00
10.27	Providing and fixing C. I. manhole cover 600mm x 450mm size having weight not less than 35kg.	3.00	No	1059.00	3177.00
10.28	Providing and fixing a set of 6 No of stainless steel coat racks of approved quality fixed on 20 mm thick Teak wood batten at 150 mm c/c including 3 coats of oil painting etc complete (450 mm long)	12.00	No	44.00	528.00
10.29	Providing and fixing brick on flooring laid dry grouted with CM (1:6) including finishing the joints flush, curing, etc complete.	15.00	Smt	257.00	3855.00
10.30	Providing 2500mm internal diameters & 4.00 Mt deep soak pit including excavation in all types of soil & soft rock & B.B.C.C. (1:4:8) bedding 300mm thick below masonry and 450mm thick brick masonry in C.M. (1:6) up to 600mm height 350mm thick for further 600mm & 230mm thick for remaining height honey combed, plastering in C.M.(1:3) outside up to 1.5mt height and 100mm thick RCC slab with 600x600mm CI having cover with frame, with necessary reinforcement as per design & CI vent pipe 1800mm long with brick masonry pillar 350x350x450 plastered all around filling 40 to 50mm brick bats up to 1.5Mt depth including 16mm dia MS"U" stages steps refilling including disposal of the surplus excavated earth up to the lead of 300Mt radius including 3 coats of white or colour wash to all exposed finished surface etc. completed as directed.	1.00	No	21560.00	21560.00

10.31	Providing and laying 20 to 25mm thick, both faces polished Kota Stone with all edges machine cut up to 450mm width and of required length [only one piece to be used] of approved quality for cupboard shelves including fixing the same in masonry wall by cement mortar in three sides including curing, etc complete as directed.	45.00	Smt	550.00	24750.00
10.32	Providing & fixing 50 mm dia. GI pipe as railing wherever required including fixing the necessary hold fasts at the end / middle and grouting the same in wall with concrete as directed in line and level and 3 coats of approved shade and make, etc complete as directed by EIC.	20.00	Rmt	308.00	6160.00
10.33	Providing CP ball bearing swing hub (for swing)of approved quality incl.fixing the same during casting of slab using 50x10 mmM.S. flat support as directed.	4.00	Pair	181.50	726.00
XI	Electrification				
11.01	Providing & fixing concealed point wiring with single PVC insulated flexible wire 1100 volt grade copper stranded, (FR grade) ISI mark of approved quality as per instruction of EIC. (Rates are applicable per POINT)	200.00	Number	431.00	86200.00
11.02	Providing & fixing Two in One (2+3 Pin Plug Socket) 5Amp. 250 Volt ISI mark plug socket with switch on same switchboard provided for item no.1 including necessary wiring & adequate earthing wire as per specification & instructions.	30	Number	86	2580.00
11.03	Providing & fixing Two in One (2+3 Pin Plug Socket) 15Amp. 250 Volt ISI mark plug socket with switch on same switchboard provided for item no.1 including necessary wiring & adequate earthing wire as per specification & instructions.	8	Number	364	2912.00
11.04	Providing & laying External wiring (concealed 1 ph wiring Upto 2 KW Loading) from main switch /intermediate joint (wire) to Room by using standard PVC pipe with separate ,mains/neutral complete as directed by E.I.C.	50	Meter	112	5600.00
11.05	Labour charges for fixing of Fans & fixtures (Ceiling & wall Mounted)	10	Number	30	300.00
11.06	Providing of earthing with 1.3 mtr 3" dia CI pipe with Collars/ connection arrangement for making rigid connection to external G.I. Flats. The Flat will be supplied by the company.	2	Number	2200	4400.00
11.07	Providing of ceiling fans : energy efficient 3 star and above of any standard ISI Mark like Crompton/ Philips/ Bajaj/Orient/Polar etc	20	Number	1550	31000.00
11.08	Providing & fixing 4 feet T-5 type complete tubelight (28 watts)	40	Number	310	12400.00
11.09	Providing & fixing hum free step dimmer for Fan.	20	Number	235	4700.00
11.1	Providing & laying 3 phase line with 4.0sqmm wire fourline (3 phase+ 1 neutral) & 2.5 sqmm wire for earthing in concealed wire with 1.0sqmm pipe 1.5 mm thick from busbar to Distribution MCB Board etc complete.	25	Meter	205	5125.00
11.11	Mains service with 1.1KV grade FRP PVC insulated ISI marked Stranded flexible copper conductor wire 2core 2.5 sqmm	25	Meter	45	1125.00
11.12	Providing & fixing 63A TPN MCB Hagger Make	10	Number	1300	13000.00

11.13	Providing & fixing 32 A DP MCB Hagger Make	12	Number	450	5400.00
11.14	Providing & fixing 20 SP MCB Hagger Make	10	Number	200	2000.00
11.15	Providing & fixing 16SP MCB Hagger Make	10	Number	200	2000.00
11.16	Providing & fixing 10SP MCB Hagger Make	15	Number	200	3000.00
11.17	Providing & fixing 3/4 pole MCB Box with 1 nos 3 phase MCB 63 AMP as per instruction of E.I.C	6	Number	2085	12510.00
11.18	Providing & fixing 3/4 pole MCB Box with 1 nos 3 phase MCB 100 AMP as per instruction of E.I.C	4	Number	2815	11260.00
11.19	Providing & fixing 3/4 pole MCB Box with 1 nos 3 phase MCB 200 AMP as per instruction of E.I.C	2	Number	4750	9500.00
11.2	Providing & fixing one door bell as per instruction of E.I.C.	4	Number	95	380.00
				RS.	5276074.80

RUPPES IN WORDS : Fifty two lacs seventy six thousand seventy four & eighty paise only.

SIGNATURE OF CONTRACTOR (With rubber stamp/seal of the company)	(With Chief Engineer (Operation) UGVCL R.O. MEHSANA
--	---

163,645.00

