





CIN – U40102GJ2003SGC042906,GST No.-24AAACU6551F1ZI

| Annua | Rate Contract for Labour charges for underground work in Mehsana City SDN Under M PR NO:-414517 | - | - | cable of a | pproved work |
|--------|---|------|----------|-------------------------------|---------------------------|
| Sr.No. | Description | Unit | Quantity | Rate per Unit in Rs. | Total Amount in Rs. |
| 1 | Laying (including installation, testing and commissioning) of various size of Single circuit 11 KV XLPE insulated Alluminum armoured Cable in ground 1200 mm deep and 300 mm wide trench, providing sand cushioning below (75 mm thick layer of sand) and above (75 mm thick layer of sand) of the cable and covering it with RCC half round Hume pipe (150 mm inner diameter with thickness of 30 mm and One meter in length) before refilling pre-bonding tap/warning tap should provide below 700 mm from the ground level and back filling the same to make ground level as per original. As per specification and drawing of UGVCL. (RCC half round pipe should be provide throughout on cable without gap). Only Cable will be supplied by UGVCL. | MTR | 1000 | 335 | 335000.00 |
| 2 | Laying (including installation, testing and commissioning) of various size of Double circuit 11 KV XLPE insulated Aluminum armoured Cable in ground in single trench 1200 mm deep and 500 mm wide trench, providing sand cushioning below (75 mm thick layer of sand) and above (75 mm thick layer of sand) of the cable and covering it with RCC half round Hume pipe (150 mm inner diameter with thickness of 30 mm and One meter in length) before refilling pre-bonding tap/warning tap should provide below 700 mm from the ground level and back filling the same to make ground level as per original. As per specification and drawing of UGVCL. (RCC half round pipe should be provide throughout on cable without gap). Only Cable will be Supplied by UGVCL. | MTR | 250 | 468 | 117000.00 |
| 3 | Labour work for laying of HT cable open from air grounding to gentry including carting. | MTR | 10 | 38 | 380.00 |







| 4 | Supply and Installation of clamps made from 50*6 mm GI flat (Minimum weight of flat 1.6 Kg per Set) for fitting for 110 mm GI/HDPE Pipe above ground with the Pole including cost of nuts & bolts. | SET | 10 | 130 | 1300.00 |
|----|--|-----|----|------|----------|
| 5 | Supply and Installation of clamps made from 50*6 mm GI flat (Minimum weight of flat 1.8 Kg per Set) for fitting for 160 mm GI/HDPE Pipe above ground with the Pole including cost of nuts & bolts. | SET | 10 | 150 | 1500.00 |
| 6 | Laying of various sizes of 11 KV XLPE insulated Aluminium armoured Cable in Cable Tray/ Trench over/below the ground level excluding Cable Tray/Trench. | MTR | 10 | 150 | 1500.00 |
| 7 | Laying of HDPE Pipe confirming to IS 4984:1955 (Amendment no. 2) having 160 mm Diameter and minimum 5 mm Thickness at a minimum Depth of 1200 mm below the road surface by Push through method, drilling the road with HDD machine/manually without breaking the road surface and laying of any size of HT XLPE insulated Aluminum armoured Cable through the duct as per the instruction of EIC and specifications excluding cost of HDPE Pipe. Only Cable will be supplied by UGVCL. (For 240 & 300 mm2 XLPE cable) | MTR | 20 | 800 | 16000.00 |
| 8 | Supply of HDPE Pipe having 160 mm Diameter and minimum 5 mm Thickness confirming to IS 4984:1955 (Amendment no. 2) for laying of 11 KV XLPE Cable. | MTR | 20 | 640 | 12800.00 |
| 9 | Laying of HDPE Pipe confirming to IS 4984:1955 (Amendment no. 2) having 160 mm Diameter and minimum 5 mm Thickness at a minimum Depth of 1200 mm below the road surface by Push through method, drilling the road with HDD machine/manually without breaking the road surface and laying of any size of HT XLPE insulated Aluminum armoured Cable through the duct as per the instruction of EIC and specifications including cost of HDPE Pipe. Only Cable will be supplied by UGVCL. | MTR | 20 | 1440 | 28800.00 |
| 10 | Laying of HDPE Pipe confirming to IS 4984:1955 (Amendment no. 2) having 110 mm Diameter and minimum 5 mm Thickness at a minimum Depth of 1200 mm below the road surface by Push through method, drilling the road with HDD | MTR | 20 | 1350 | 27000.00 |







CIN – U40102GJ2003SGC042906,GST No.-24AAACU6551F1ZI

| | | | | 1 | |
|----|---|-----|------|------|-----------|
| | machine/manually without breaking the road surface and laying of any size of HT XLPE insulated Aluminum armoured Cable through the duct as per the instruction of EIC and specifications excluding cost of HDPE Pipe. Only Cable will be supplied by UGVCL. | | | | |
| 11 | Supply of HDPE Pipe having 110 mm Diameter and minimum 5 mm Thickness confirming to IS 4984:1955 (Amendment no. 2) for laying of 11 KV XLPE Cable. | MTR | 1200 | 525 | 630000.00 |
| 12 | Laying of HDPE Pipe confirming to IS 4984:1955 (Amendment no. 2) having 110 mm Diameter and minimum 5 mm Thickness at a minimum Depth of 1200 mm below the road surface by Push through method, drilling the road with HDD machine/manually without breaking the road surface and laying of any size of HT XLPE insulated Aluminum armoured Cable through the duct as per the instruction of EIC and specifications including cost of HDPE Pipe. Only Cable will be supplied by UGVCL. (For 70 & 185 mm2 XLPE cable) | MTR | 1200 | 825 | 990000.00 |
| 13 | Laying of Medium grade GI Pipe having 110 mm Diameter at a minimum Depth of 1200 mm below the road surface by Push through method, drilling the road with HDD machine/manually without breaking the road surface and laying of any size of HT XLPE insulated Aluminum armoured Cable through the duct as per the instruction of EIC and specifications including cost of GI Pipe. Only Cable will be supplied by UGVCL. | MTR | 10 | 1240 | 12400.00 |
| 14 | Supply and Fixing of Medium grade GI Pipe having 110 mm Diameter and minimum length 2.5 meter | MTR | 20 | 925 | 18500.00 |
| 15 | Laying of Medium grade GI Pipe having 160 mm Diameter at a minimum Depth of 1200 mm below the road surface by Push through method, drilling the road with HDD machine/manually without breaking the road surface and laying of any size of HT XLPE insulated Aluminum armoured Cable through the duct as per the instruction of EIC and specifications including cost of GI Pipe. Only Cable will be supplied by UGVCL. | MTR | 10 | 1490 | 14900.00 |
| 16 | Supply and Fixing of Medium grade GI Pipe having 160 mm Diameter and minimum length 2.5 meter | MTR | 10 | 800 | 8000.00 |
| 17 | Providing and Fixing of Heat Shrikable Indoor | NO | | | |

Schedule - B







CIN – U40102GJ2003SGC042906,GST No.-24AAACU6551F1ZI

| Cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO147184718.00A70 mm2 HT XLPE CableNO5495324765.00C240 mm2 HT XLPE CableNO5525226260.00D300 mm2 HT XLPE CableNO155495549.00Providing and Fixing of Heat Shrikable Outdoor Termination KIts for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons/ Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO156645664.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for of 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)777A70 mm2 HT XLPE CableNO180408040.0019185 mm2 HT XLP | | Termination Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of | | | | |
|---|----|--|-----|----|------|----------|
| terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO147184718.00A70 mm2 HT XLPE CableNO5495324765.00C240 mm2 HT XLPE CableNO5525226260.00D300 mm2 HT XLPE CableNO155495549.00Providing and Fixing of Heat Shrikable Outdoor Termination Kits for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type | | | | | | |
| Densons / Vikchem etc.)NO14718.4718.00A70 mm2 HT XLPE CableNO14718.4718.00B185 mm2 HT XLPE CableNO5525226260.00D300 mm2 HT XLPE CableNO155495549.00Providing and Fixing of Heat Shrikable Outdoor Termination Kits for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO156645664.00D300 mm2 HT XLPE CableNO166766676.00C240 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO18040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distanc | | | | | | |
| A70 mm2 HT XLPE CableNO147184718.00B185 mm2 HT XLPE CableNO5495324765.00C240 mm2 HT XLPE CableNO5525226260.00D300 mm2 HT XLPE CableNO155495549.00Providing and Fixing of Heat Shrikable Outdoor Termination Kits for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointig Kits for 67 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00300 mm2 HT XLPE CableNO18040.00PA70 mm2 HT XLPE CableNO180408040.0010300 mm2 HT XLPE CableNO180408040.000300 mm2 HT XLPE CableNO1804 | | tool. (Quality make of Raychem / 3M (M-Seal) / | | | | |
| B185 mm2 HT XLPE CableNO5495324765.00C240 mm2 HT XLPE CableNO5525226260.00D300 mm2 HT XLPE CableNO155495549.00Providing and Fixing of Heat Shrikable Outdoor Termination Kits for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO166766676.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00A70 mm2 HT XLPE CableNO171997199.00A70 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00A70 mm2 HT XLPE CableNO | | Densons / Vikchem etc.) | | | | |
| C240 mm2 HT XLPE CableNO5525226260.00D300 mm2 HT XLPE CableNO155495549.00Providing and Fixing of Heat Shrikable Outdoor Termination Kits for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO166766676.00D300 mm2 HT XLPE CableNO166766676.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for 0 -3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO1765538275.00C240 mm2 HT XLPE CableNO5785039400.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO< | А | 70 mm2 HT XLPE Cable | NO | 1 | 4718 | 4718.00 |
| D300 mm2 HT XLPE CableNO155495549.00Providing and Fixing of Heat Shrikable Outdoor Termination Kits for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO171997199.00A70 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00A70 mm2 HT XLPE CableNO180408040.00A70 mm2 HT XLPE CableNO180408040.00A70 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO1 </td <td>В</td> <td>185 mm2 HT XLPE Cable</td> <td>NO</td> <td>5</td> <td>4953</td> <td>24765.00</td> | В | 185 mm2 HT XLPE Cable | NO | 5 | 4953 | 24765.00 |
| Providing and Fixing of Heat Shrikable Outdoor Termination Kits for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO166766676.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO <t< td=""><td>С</td><td>240 mm2 HT XLPE Cable</td><td>NO</td><td>5</td><td>5252</td><td>26260.00</td></t<> | С | 240 mm2 HT XLPE Cable | NO | 5 | 5252 | 26260.00 |
| Termination Kits for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO1598271784.00C240 mm2 HT XLPE CableNO166766676.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO18040.00C240 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO18040.00D300 mm2 HT XLPE CableNO18040.00C240 mm2 HT XLPE CableNO18040.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO18040.00120Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below | D | 300 mm2 HT XLPE Cable | NO | 1 | 5549 | 5549.00 |
| Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO156645664.00C240 mm2 HT XLPE CableNO5637831890.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00A70 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00C240 mm2 HT XLPE CableNO180408040.00A70 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO | | Providing and Fixing of Heat Shrikable Outdoor | | | | |
| 18connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)Image: Connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO166766676.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00A70 mm2 HT XLPE CableNO180408040.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE Cable | | Termination Kits for 3-Core, 11 KV XLPE | | | | |
| 18cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO166766676.00D300 mm2 HT XLPE CableNO166766676.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO18040 <td></td> <td>Aluminium armoured Cable as specified with</td> <td></td> <td></td> <td></td> <td></td> | | Aluminium armoured Cable as specified with | | | | |
| Cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO5637831890.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC <br< td=""><td>18</td><td>connection of leads including cutting, stripping of</td><td></td><td></td><td></td><td></td></br<> | 18 | connection of leads including cutting, stripping of | | | | |
| tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO156645664.00A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO5637831890.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2: | 10 | | | | | |
| Densons / Vikchem etc.)Image: constraint of the second | | | | | | |
| A70 mm2 HT XLPE CableNO156645664.00B185 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO5637831890.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone – "UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | | | | | | |
| B185 mm2 HT XLPE CableNO12598271784.00C240 mm2 HT XLPE CableNO5637831890.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete st | | | | | | |
| C240 mm2 HT XLPE CableNO5637831890.00D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00C240 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone –"UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 <td>Α</td> <td>70 mm2 HT XLPE Cable</td> <td>NO</td> <td>1</td> <td>5664</td> <td>5664.00</td> | Α | 70 mm2 HT XLPE Cable | NO | 1 | 5664 | 5664.00 |
| D300 mm2 HT XLPE CableNO166766676.00Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone -"UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | | 185 mm2 HT XLPE Cable | NO | 12 | 5982 | 71784.00 |
| Providing and Fixing of Heat ShrikableStright Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone -"UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | С | 240 mm2 HT XLPE Cable | NO | 5 | 6378 | 31890.00 |
| Jointing Kits for for 3-Core, 11 KV XLPE Aluminium armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)Image: Comparison of the terminal of terminal of the terminal of the terminal of terminal of the terminal of terminal of terminal of terminal of terminal of terminal of the terminal of the terminal of | D | 300 mm2 HT XLPE Cable | NO | 1 | 6676 | 6676.00 |
| armoured Cable as specified with connection of leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)Image: Comparison of the terminal of termina | | Providing and Fixing of Heat ShrikableStright | | | | |
| 19leads including cutting, stripping of cable, insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)Image: Compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone -"UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | | Jointing Kits for for 3-Core, 11 KV XLPE Aluminium | | | | |
| 19insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)Image: Comparison of Comparison | | | | | | |
| Insulations, providing compression type terminal, crimping of lugs with suitable crimping tool. (Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)< | 19 | | | | | |
| Quality make of Raychem / 3M (M-Seal) / Densons / Vikchem etc.)NO171997199.00A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone"UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | 15 | | | | | |
| Densons / Vikchem etc.)Image: Constraint of the system of the | | | | | | |
| A70 mm2 HT XLPE CableNO171997199.00B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC1:2:4, 150 mm X 150 mm X 750 mm Concrete8040.008040.0020Providing and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone -"UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | | | | | | |
| B185 mm2 HT XLPE CableNO5765538275.00C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone"UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | | Densons / Vikchem etc.) | | | | |
| C240 mm2 HT XLPE CableNO5788039400.00D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone - "UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | A | 70 mm2 HT XLPE Cable | NO | 1 | 7199 | 7199.00 |
| D300 mm2 HT XLPE CableNO180408040.00Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone - "UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | | 185 mm2 HT XLPE Cable | NO | | 7655 | 38275.00 |
| Providing and Fixing of "Route marker" of CC 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone – "UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | C | 240 mm2 HT XLPE Cable | NO | 5 | 7880 | 39400.00 |
| 1:2:4, 150 mm X 150 mm X 750 mm Concrete stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone – "UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | D | | NO | 1 | 8040 | 8040.00 |
| stone embedded in earth at least 300 mm below the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone – "UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | | Providing and Fixing of "Route marker" of CC | | | | |
| 20the GL and 450 mm above GL at distance of approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone | | 1:2:4, 150 mm X 150 mm X 750 mm Concrete | | | | |
| 20approximately 100 Meter or as directed by engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone – "UGVCL 11 KV Cable" including material, painting &labourMTR3040012000.00 | 20 | | | 30 | | |
| 20 engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone –"UGVCL 11 KV Cable" including material, painting &labour MIR 30 400 12000.00 | | | MTR | | 400 | |
| engineer in charge. The route marker must be painted with yellow colour of stone with red colour for embracing on stone –"UGVCL 11 KV Cable" including material, painting &labour | | | | | | 12000.00 |
| colour for embracing on stone –"UGVCL 11 KV Cable" including material, painting &labour | | | | | | |
| Cable" including material, painting &labour | | | | | | |
| | | - | | | | |
| charges for excavation& refilling. | | | | | | |
| Schedule - B | | • | | | | |







CIN – U40102GJ2003SGC042906,GST No.-24AAACU6551F1ZI

| TOTAL AMOUNT OF TENDER = Rs. | | | | |
|------------------------------|--|--|--|--|

Schedule - B